PORTINO TO STANDARDO TO STANDAR





The Towering Beauty

With its prominent stature and distinctive nature, Portino unveils Portino Plus to add a new expression of vastness to your space.

Inspired by the towering beauty of mother nature, Portino Plus brings the raw and eclectic look of natural surfaces to uplift and enhance the aesthetics of your interiors.


The "Plus" in its namesake not only refers to its large format size but also the depth and grandeur it adds to its surroundings. Outstanding and breath-taking with each of its varied and tasteful designs, be transported each time you lay your sights upon these pieces.











NEW EXPRESSION OF VASTNESS

FLOOR: PPS01 ARIELLE . 90x180cm . polishe



FLOOR: PPS02 AVERY . 90x180cm . polished + PPS03 AYLIN . 90x180cm . soft polished 90x180cm





OUTSTANDING AND BREATH-TAKING FLOOR: PPSO3 AYLIN . 90x 180cm . soft polished











PREFECT SIZE FOR YOUR WALL

FLOOR: PPS72 ASHLEY . 75x150cm . structured WALL: PPS71 AYDEN . 75x150cm . polished











Arielle

PPS01 90x180cm . Polished V3









Avery PPS02 90x180cm . Polished V3










Aylin PPS03 90x180cm . Soft Polished V3









Alyce PPS04 90x180cm. Polished V2








Ayden PPS71 75x150cm . Polished V3

























PPS74 75x150cm . Matt V2













PPS76 75x150cm . Polished V2











PPS77 75x150cm . Polished V2












PPS78 75x150cm . Polished V2
















PORTINO TECHNICAL SPECIFICATION

DESCRIPTION	STANDARD TEST	MEASUREMENT UNIT	PORCELAIN (Group Bla)			
			mm	Rectified	mm	Non Rectified
Length & Width	MS ISO 10545-2	mm	±1.0	±0.30%	±2.0	±0.60%
Thickness	MS ISO 10545-2	mm	±0.5	±5.00%	±0.5	±5.00%
Sides Straightness	MS ISO 10545-2	mm	±0.8	±0.30%	±1.5	±0.50%
Rectangularity	MS ISO 10545-2	mm	±1.5	±0.30%	±2.0	±0.50%
Flatness: a) Centre curvature	MS ISO 10545-2	mm	±1.8	±0.40%	±2.0	±0.50%
b) Edge curvature	MS ISO 10545-2	mm	±1.8	±0.40%	±2.0	±0.50%
c) Warpage	MS ISO 10545-2	mm	±1.8	±0.40%	±2.0	±0.50%
Surface Quality	MS ISO 10545-2	One Major Area of Tiles	Min. 95% free from defects			
Water Absorption	MS ISO 10545-3	Mass	Ev ≤ 0.5%			
Breaking Strength : a) Thickness ≥ 7.5mm	MS ISO 10545-4	N	Not less than 1300N			
b) Thickness < 7.5mm	MS ISO 10545-4	N	Not less than 700N			
Modulus of Rupture : a) Thickness ≥ 7.5mm	MS ISO 10545-4	N/mm2	Minimum 35			
b) Thickness < 7.5mm	MS ISO 10545-4	N/mm2	Individual Minimum 32			
Abrasion Resistance Surfaces Abrasion for glazed tiles	MS ISO 10545-7	Visual Check	≥ PEI 3 (Dependent on product type)*			
Crazing Test (glazed tiles)'	MS ISO 10545-11	Visual Check	Required			
Frost Resistance	MS ISO 10545-12	Visual Check	Required			
Chemical Resistance a) Low concentrations	MS ISO 10545-13	Visual Check	Manuf. To State			
b) Household chemicals and swimming pool salts	MS ISO 10545-13	Visual Check	Minimum B			
Stain Resistance For glazed tiles	MS ISO 10545-14	Visual Check	Minimum class 3			
Slip Resistance (Excluding Polished, Lappato and matt Satin finishing)	AS/NZS 4586 App.A	Visual Check	Wet Pendulum ≤ P2 (Dependent on product type)*			

Each different tile series are produced to meet different performance requirements. For specific product technical performance, please request from Portino sales team, their agent or distributor. The tile designs in each carton are random and may or may not be the same.

Colour Variations: Since the colour reproduction in this printed piece will vary from the actual tile colours, final selection should be made from tile samples Colour, shade and glaze variations may exist due to the inherent characteristics of porcelain tile.

Due to the low porosity of porcelain tiles, an Improved High Performance Cementitious adhesive in accordance to BS/EN 12004 & ISO 13007-1 is highly recommended for proper installation. Products that meet this standard are available amongst leading adhesive manufacturers. Please seek expert advice from adhesive manufacturers for proper selection and application.



SHADE VARIATION









MODERATELY NOTICEABLE FROM TILE TO TILE



DISTINCTLY NOTICEABLE FROM TILE TO TILE













NIRO CERAMIC GROUP

Lot 2, Persiaran Sultan, Seksyen 15, 40200 Shah Alam, Selangor, Malaysia. T +603 5033 9333 F +603 5033 9323

www.nirogranite.com





